

Microengine GT3500L

1. Card User Memory	3,500
2. Transaction Records	20,000
3. Single Unit Reader, Keypad & Controller	Yes
4. Build-In Card Reader	Yes – EM Card (Mifare Card Model Available) Card Only, Card + PIN, Fingerprint
5. Access Operation Mode	Card + Fingerprint, PIN + Fingerprint Card + PIN + Fingerprint
6. Fingerprint Template Capacity	3200
1:N	1:3200
7. Display	128 x 64 Graphic Display with Back Light
8. Keypad	Touch Sense Keypad with Backlight
9. Time Set & Time Zone	Yes (10 set)
10. Holiday Dates	30
11. Auto PIN	Not Available
12. Built-in Real Time Clock with Battery	Yes
13. Car Park Mode External Entry Reader	No
14. Exit Reader	Yes – Use MAS-RBT to connect the Entry and Exit Unit
15. Exit Push Button	Yes – with Time Zone Control
16. Support Wiegand 26-bit Reader	Yes
17. Anti-Passback	Yes
18. Controller Operation Mode	Access Control Mode
19. Supports Programming Through Keypad & LCD at the Reader	Yes
20. Lock Control, Door Sensor & Exit Button Input	Yes – Through MAS-RBS Located Inside the Door
21. Configurable Lock Release Time	Yes – 0-99 secs.
22. Configurable Door Open Time	Yes – 0-99 secs.
23. Auto Lock Release Time Zone	Yes
24. Sensor & Output	No
25. Data Flash Memory	32MBit
26. Onboard Buzzer	Yes
27. Communication Ports	RS485 / LAN
28. Can be Linked to PC for Software Control	Yes
29. Power	12VDC
30. Dimension	131mm (H) x 158mm (W) x 65mm (D)